GS1 GS to ~ w CR with Factory Reset: Programming Barcodes for DS2208

Configuration name in Utility :	GS1 GS to ~ w CR
Last Modified :	02-Mar-26
Windows Filename :	Config File_DS2208_GS1 GS to ~ w CR_
Plug-in Name :	2026.03.02.scncfg
ADF Version :	DS2208-COMMON SR MODELS-019
Report Type :	v2.0
	Only parameters changed from defaults shown

Note: This programming will only be applied to selected Scanner/“Plugin Release” numbers. Your scanner must support ADF2.0, for details see “Release Notes”

Set Factory Defaults

Symbology (bar code type) Settings

DataMatrix

GS1-Datamatrix	Enable

Modify Data- Advanced Data Formatting

Erase All Rules

Begin new Rule with Criteria Sections = 1

Criteria Section : 1

1. Replace Character <CTRL]/GROUP SEPERATOR> with <~>

2. Replace Character <CTRL]/GROUP SEPERATOR> with <~>

3. Replace Character <CTRL]/GROUP SEPERATOR> with <~>

4. Send All that remains

5. Send Extended Key <Enter>

Save Rule

General Parameter Settings

Configuration File	GS1 GS to ~ w CR

Notes:

GS1 DataMatrix
- Factory Reset
- Erase All Rules
- Replace <GS> with Tilda (~)
- Send Carriage Return

Firmware:

CAADES00-008-R00